SUN5-2KVA OFF-GRID HYBRID INVERTER

- Pure sine wave solar inverter
- Output power factor 1
- Selectable high power charging current
- Wide DC input range
- Selectable input voltage range for home appliances
- Configurable AC/Solar input priority via LCD setting
- Compatible to AC mains or generator power
- Auto restart while AC is recovering
- Overload and short circuit protection
- Battery equalization for optimized battery performance



MODEL	SUN5 2K PWM
RATED POWER	2000VA/2000W
INPUT	
Voltage	230 VAC
Selectable Voltage Range	170-280 VAC (For Personal Computers) ; 90-280 VAC (For Home Appliances)
Frequency Range	50 Hz/60 Hz (Auto sensing)
OUTPUT	
AC Voltage Regulation (Batt. Mode)	230VAC ± 5%
Surge Power	4000VA
Efficiency (Peak)	90%
Transfer Time	10 ms (For Personal Computers) ; 20 ms (For Home Appliances)
Waveform	Pure sine wave
BATTERY	
Battery Voltage	24 VDC
Floating Charge Voltage	27 VDC
Overcharge Protection	31 VDC
SOLAR CHARGER & AC CHARGER	
Solar Charger type	PWM
Maximum PV Array Open Circuit Voltage	80 VDC
Maximum PV Array Power	1200 W
MPP Range @ Operating Voltage	N/A
Maximum Solar Charge Current	50 A
Maximum AC Charge Current	20 A
Maximum Charge Current	50 A
PHYSICAL	
Dimension, D x W x H (mm)	88 x 225 x 320
Net Weight (kgs)	5
Communication Interface	USB/RS232
ENVIRONMENT	
Humidity	5% to 95% Relative Humidity (Non-condensing)
Operating Temperature	-10°C to 50°C
Storage Temperature	-15°C to 60°C