SUN5-3KVA MPPT Off-Grid HYBRID INVERTER

- Pure sine wave solar inverter
- Output power factor 1
- Selectable high power charging current
- Wide DC input range
- Selectable input voltage range for home appliances
- Configurable AC/Solar input priority via LCD setting
- Compatible to AC mains or generator power
- Auto restart while AC is recovering
- Overload and short circuit protection
- Battery equalization for optimized battery performance



MODEL	SUN5 3K- MPPT Plus
RATED POWER	3000VA / 3000W
INPUT	
Voltage	230 VAC
Selectable Voltage Range	170-280 VAC (For Personal Computers) ; 90-280 VAC (For Home Appliances)
Frequency Range	50 Hz/60 Hz (Auto sensing)
OUTPUT	
AC Voltage Regulation (Batt. Mode)	230VAC ± 5%
Surge Power	6000VA
Efficiency (Peak)	93%
Transfer Time	10 ms (For Personal Computers) ; 20 ms (For Home Appliances)
Waveform	Pure sine wave
BATTERY	
Battery Voltage	24 VDC
Floating Charge Voltage	27 VDC
Overcharge Protection	33 VDC
SOLAR CHARGER & AC CHARGER	
Solar Charger type	MPPT
Maximum PV Array Open Circuit Voltage	145 VDC
Maximum PV Array Power	1500 W
MPP Range @ Operating Voltage	30~115 VDC
Maximum Solar Charge Current	60 A
Maximum AC Charge Current	60 A
Maximum Charge Current	120 A
PHYSICAL	
Dimension, D x W x H (mm)	100 x 300 x 440
Net Weight (kgs)	9.5
Communication Interface	USB/RS232
ENVIRONMENT	
Humidity	5% to 95% Relative Humidity (Non-condensing)
Operating Temperature	-10°C to 50°C
Storage Temperature	-15°C to 60°C